

This technical data sheet is based upon the CSC Manu-Data® format.

May 2022

**1. Product Name**

Enviroshingle Roofing

**2. Manufacturer**

Enviroshake  
 1130 Wellington Street  
 Dresden ON N0P 1M0  
 Canada  
 Phone: 1 (519) 380-9265  
 Toll Free: (866) 423-3302  
 FAX: 1 (519) 380-0689  
 e-mail: [info@enviroshake.com](mailto:info@enviroshake.com) .  
 URL: <http://www.enviroshake.com>



**Enviroshingle Installation in Accora Village**

**3. Product Description**

**DESCRIPTION**

Enviroshingle is a composite roof shingle that authentically emulates the look of a natural perfection cedar shingles that competes in the specialty and premium roof markets.

**BASIC USE**

Enviroshingle composite shingles are used for roofing and siding applications. Properly installed shingles provide long lasting weather protection and a rustic aesthetic look weatherproofing system.

**BENEFITS**

Enviroshingle gives the pleasing aesthetic of cedar shingles with lifetime performance and with minimal amount of maintenance.

The 2 profiles that the Enviroshingle comes in are made from the 3D images of real cedar shingles, to ensure the wood grains, thickness, and sizes are all true to nature.

They come in three tones: Aged Cedar, Silvered Cedar, and Tropical Silver that weather with exposure to UV, and as with cedar, there will be variations in shading to provide a natural look on the roof.

No special tools are needed to install Enviroshingle composite shingle roofing.

Enviroshingle comes in Gold and Standard Level warranties with a lifetime warranty for residential applications and a 50-year warranty for commercial applications, 25-year warranty for Caribbean applications. See Warranty Document for more information.

**LIMITATIONS**

Enviroshingle should not be installed over existing asphalt shingles, or OSB or roof slopes less than 2:12.

**TYPES AND SIZES**

Enviroshingle comes in lengths of 20”, each with a width of 12”. The shingles are shrink-wrapped on skids (84 bundles per skid) for shipping. Each bundle contains 7 pieces of varied profiles. There are 20 bundles to a “Square” at a 5¼” exposure. Ridge caps are 12”-wide one-piece shingles, custom formed to the specification of the roof slope and are packaged in bundles of 10 pieces.

**COVERAGE**

1 square covers 100 square feet when installed at a 5¼” exposure. The minimum slope is 2:12. There is no limit on the maximum slope.

**4. Technical Data**

This technical data sheet is based upon the CSC Manu-Data® format.

May 2022

Copies of test procedures and results are available upon request.

International Conference of Building Officials (ICC) Acceptance Criteria for Special Roofing Systems- Protocol AC07		Building Materials Evaluation Commission (BMEC) Dec. 1999	
Testing Procedure	Standard	Testing Procedure	Standard
1. Weatherometer	ASTM G23 ASTM G26 ASTM D790	1. Impact Testing	ASTM D2794
2. Roof classification		2. Water Absorption	ASTM D570
-fire retardant	UBC Standard 15-2 ICBO 4.9	3. Wind Resistance	ASTM D3161
Accelerated weathering and ignition/burning rate tests	UBC Standard 26-6 UBC Standard 26-7 ICBO 4.9	4. Tear Strength/Nail Head Resistance	ASTM D1037
3. Wind Uplift	Any test (dynamic, static and structural calculations)	5. UV Exposure	ASTM G-53
4. Wind-Driven Rain	ICBO 4.3	6. Freeze Thaw	ASTM C666
5. Uplift-Bend	ICBO 4.4		
6. Penetration	ICBO 4.2		
7. Temperature-cycling	ICBO 4.8		
8. Flexural strength	ICBO 3.5.2 UBC Standard 15-5		



Enviroshingle

This technical data sheet is based upon the CSC Manu-Data® format.

May 2022

#### APPLICABLE STANDARDS

##### ASTM International

- ASTM D7349/D7349M, Standard Test Method for Determining the Capability of Roofing and Waterproofing Materials to Seal around Fasteners.
- ASTM E108, Standard Test Methods for Fire Tests of Roof Coverings.

##### Canadian General Standards Board (CGSB)

- CGSB-37.58-M86, Membrane, Elastomeric, Cold-Applied Liquid, for Non-Exposed Use in Roofing and Waterproofing.

##### Florida Building Code Testing Application Standard (TAS)

- TAS-125- Test for Uplift Resistance on Roof Assemblies

##### Miami-Dade Construction Standards (DADE)

- DADE PA 100-[2000], Test Procedure for Wind and Wind Driven Rain Resistance of Discontinuous Roof Systems.

##### Underwriter's Laboratories

- UL 2218, Impact Resistance of Prepared Roof Covering Materials, Class 4.

##### US Green Building Council

- USGBC: LEED® NC Version 2.2.

#### APPROVALS

- American Society for Testing and Materials Limited.
- California Building Materials Listing No. 4175-2114:0100
- Florida Building Code FL#16037-R2
- Miami Dade County NOA No. 19-0807.04
- National Building Code of Canada.
- Canadian General Standards Board: Stability Testing - Products are tested

at temperature cycles ranging from -40°F (-40°C) to 160°F (71°C).

- National Building Code of Canada.
- Uniform Building Code: UV Testing - 2000 hours of accelerated weathering tests are completed to ensure no evidence of change in physical properties

#### ENVIRONMENTAL CONSIDERATIONS

Enviroshingle composite roofing shingles are slippery when wet. Do not walk on Enviroshingle composite roofing shingles while they are rain, ice, frost or snow covered.

#### SUSTAINABILITY CONSIDERATIONS

For information on LEED Prerequisites and Credits associated with this product, refer to the "LEED Brochure on the Enviroshake® Inc. web site at <http://www.enviroshake.com>.

#### 5. Installation

Enviroshingle should be installed as a new roofing system.

Install drip edge, valley and ridge flashings, eaves protection and synthetic underlayment before installing shingles (a 36" ice and water shield membrane is used on eaves, valleys, rakes, hips and ridges). Enviroshield synthetic underlayment is a requirement to achieve Gold Level Warranty.

Use double starter course at bottom edges, including vertical and high slope roof surfaces.

Fasten each shingle with four 1½" stainless steel nails minimum regardless of shingle

width. Although stainless steel nails are preferred hot-dipped galvanized nails are also acceptable.



Lay each consecutive row of shingles at 5¼" exposure, ensuring that there is no keyway on keyway, and that there is a ⅜" gap between every shingle (including the starter row).

Using a synthetic underlayment negates the need for interweaving.

Cut shingles to fit accurately around roof projections.

Use only uncut factory edges kept flush along rake and gable ends and where ends are exposed.

Install prefinished soffits and fascia material where indicated.

Install roof ventilators and other roofing accessories where indicated.

When using a ridge venting system, drop the ridge cap slope by 1 size.

The minimum roof slope on which Enviroshingle is recommended is 2:12. For more detailed installation instructions refer to the Enviroshingle Installation Guide.

**6. Availability and Costs**

**AVAILABILITY**

Order composite roof shingles 2 – 4 weeks before required delivery dates.

**COSTS**

Contact Enviroshake for current product costs.

**7. Warranty**

Enviroshake comes in Gold and Standard Level warranties with a 50-year warranty for commercial installations and limited lifetime warranty for residential installations. (Caribbean applications have a 25-year warranty)

Warranty is dependent upon installation by a Factory Trained Enviroshake Installer. Please see Warranty Document for further details.

**8. Maintenance**

Composite shake roofing should be regularly inspected for organic built up and should be removed from the roof. No special tools are required for roof maintenance.

**9. Technical Services**

Technical representative will visit project site as required during construction.

**10. Filing Systems**

- MasterFormat™ 07 31 34.
- OmniClass™  
Table 21 02 10 20 90.  
Table 22 07 31 34.  
Table 23 13 39 21.

